

Specifications

Specifications are valid under the following settings and conditions, unless otherwise noted.

Load : Resistance load of power factor 1, Signal source: INT (internal signal source),
Output voltage waveform : Sine wave, Remote sensing : Off, AGC/Autocal : Off,
Current Limiter : Factory default setting

- [set] indicates a setting value, and [rdg] indicates a read value.
The description noted with "/" indicates that the specification changes by the output range, such as "100 V range specification / 200 V range specification."
- The input voltage is noted as line voltage in three-phase four-wire input, unless otherwise noted.
- A value with the accuracy is the guaranteed value of the specification.
- A value without the accuracy is the nominal value or representative value (shown as typ.) .
- 1P2W: Single-phase, 1P3W: Single-phase, Three-wire, 3P3W: Three-phase, Three-wire, 3P4W: Three-phase, Four-wire

AC/DC Mode and Signal Source

	Single-phase output	Polyphase system
AC/DC mode	AC, ACDC, DC	AC, ACDC
Signal source	INT, VCA, SYNC, EXT, ADD	INT, VCA, SYNC

Power Output

	DP420LS		DP480LS	
	Single-phase	Polyphase	Single-phase	Polyphase
Multi-phase output				
Power capacity	42 kVA		48 kVA	
Mode	1P2W Floating output, the Lo terminal can be grounded.	1P3W 3P4W (Y-connection) Floating output, the N-terminal can be grounded.	1P2W Floating output, the Lo terminal can be grounded.	1P3W 3P4W (Y-connection) Floating output, the N-terminal can be grounded.
Setting mode *1	—	Balanced, Unbalanced	—	Balanced, Unbalanced
Rated output voltage	100 V / 200 V			
Voltage setting range *2	0.0 V to 160.0 V / 0.0 V to 320.0 V, Arbitrary wave : 0.0 Vp-p to 454.0 Vp-p / 0.0 Vp-p to 908.0 Vp-p(arbitrary), Setting resolution : 0.1 V			
Voltage accuracy *3	± (0.5 % of set + 0.6 V / 1.2 V)			
Line voltage setting range *4	—	1P3W : 0.0 V to 320.0 V / 0.0 V to 640.0 V 3P4W : 0.0 V to 277.2 V / 0.00 V to 554.2 V Setting resolution : 0.2 V	—	1P3W : 0.0 V to 320.0 V / 0.0 V to 640.0 V 3P4W : 0.0 V to 277.2 V / 0.00 V to 554.2 V Setting resolution : 0.2 V
Maximum current *5	420 A / 210 A		480 A / 420 A	
Maximum peak current *6	Peak value (Apk) which is three times of the maximum current			
Short reverse power flow *7 *8	100 % or less of maximum current (RMS) (reverse power flow time ≤ 20 ms, discontinuous, 40°C or lower)			
Load power factor *8	0 to 1 (phase lead or phase lag, 45 Hz to 65 Hz)			
Frequency setting range	40.00 Hz to 550.00 Hz (AC mode) , 1.00 Hz to 550.00 Hz (ACDC mode) , Setting resolution : 0.01 Hz			
Frequency accuracy	±0.01 % of set (23°C ±5°C)			
Frequency stability *9	±0.005%			
Voltage frequency characteristic*10	±1%			
Output waveform	Sine wave, arbitrary wave (16 types) , clipped sine wave (3 types)			
Output on phase setting range*11	0.0° to 359.9° variable, Setting resolution : 0.1°			
Output off phase setting range*11	0.0° to 359.9° variable (active/inactive selectable) , Setting resolution : 0.1°			
Setting range of the phase angle *12	—	1P3W L2 phase : 0.0° to 359.9° 3P4W L2 phase : 0.0° to 359.9° L3 phase : 0.0° to 359.9° Setting resolution : 0.1°	—	1P3W L2 phase : 0.0° to 359.9° 3P4W L2 phase : 0.0° to 359.9° L3 phase : 0.0° to 359.9° Setting resolution : 0.1°
Phase angle accuracy *13	—	45 Hz to 65 Hz : ±1.0° 40 Hz to 550 Hz : ±2.0°	—	45 Hz to 65 Hz : ±1.0° 40 Hz to 550 Hz : ±2.0°
DC offset *14	Within ± 20 mV (typ.), fine adjustment available			
Power capacity	42 kW	—	48 kW	—
Mode	Floating output, the Lo terminal can be grounded.	—	Floating output, the Lo terminal can be grounded.	—
Rated output voltage	100 V / 200 V	—	100 V / 200 V	—
Voltage setting range	-227 V to +227 V / -454 V to +454 V, Setting resolution : 0.1 V	—	-227 V to +227 V / -454 V to +454 V, Setting resolution : 0.1 V	—
Voltage accuracy *15	± (0.5% of set + 0.6 V / 1.2 V)	—	± (0.5% of set + 0.6 V / 1.2 V)	—
Maximum source current *16	420 A / 210 A	—	480 A / 240 A	—
Maximum instantaneous source current *17	Peak value (Apk) which is three times of the maximum current	—	Peak value (Apk) which is three times of the maximum current	—
Short sink current *18	100 % or less of maximum source current (reverse power flow time ≤ 20 ms, discontinuous, 40°C or lower)	—	100 % or less of maximum source current (reverse power flow time ≤ 20 ms, discontinuous, 40°C or lower)	—

Stability and Distortion

Output voltage stability	Fluctuation with input voltage *19 : Within ±0.15%			
	Fluctuation with output current *20			
	±0.15 V / ±0.30 V(DC)	±0.15 V / ±0.30 V(45 Hz to 65 Hz)	±0.15 V / ±0.30 V(DC)	±0.15 V / ±0.30 V(45 Hz to 65 Hz)
	±0.15 V / ±0.30 V(45 Hz to 65 Hz)	±0.15 V / ±0.30 V(45 Hz to 65 Hz)	±0.15 V / ±0.30 V(45 Hz to 65 Hz)	±0.15 V / ±0.30 V(45 Hz to 65 Hz)
Distortion of output voltage waveform *22	±0.15 V / ±1.0 V(40 Hz to 550 Hz)	±0.15 V / ±1.0 V(40 Hz to 550 Hz)	±0.15 V / ±1.0 V(40 Hz to 550 Hz)	±0.15 V / ±1.0 V(40 Hz to 550 Hz)
	Fluctuation with ambient temperature (Phase voltage) *21 : Within ±0.01 %/°C (typ.)			
	0.5 % or lower			

Power Input

	DP420LS		DP480LS	
Voltage (Specify when ordering)	Overvoltage Category II 3P3W input : 200 V to 220 V ±15 %, with limited to 250 V or lower 3P4W input : 380 V (phase voltage : 220 V) ±15 %, with limited to 433 V (phase voltage : 250 V) or lower.			
Frequency	50 Hz ±2 Hz or 60 Hz ±2 Hz			
Power factor*23	0.90 or higher (typ.)			
Efficiency *23	77% or higher (typ.)			
Maximum power consumption	63 kVA or lower	3P3W : 126 kVA or lower 3P4W : 189 kVA or lower	72 kVA or lower	3P3W : 144 kVA or lower 3P4W : 216 kVA or lower

General Specifications

	DP420LS	DP480LS
Interface	USB (USB1.1, USBTMC), RS-232 (Equipped as standard) GPIB, LAN (IEEE 802.3, LXI 1.4 Core 2011) (Specify when ordering)	
Withstand voltage	AC 1500 V or DC 2130 V 1 minute	
Operating temperature/humidity	0°C to +50°C, 5% to 85%RH (absolute humidity : 1 to 25 g/m³, without condensation) Some specifications are limited by the temperature range	
Dimensions (mm) (not including protrusions)	1365(W)×1580(H)×803(D)	
Weight	Approx. 600 kg	Approx. 650 kg
Power input terminal (rear)	M10 upset bolt	
Output terminal	M16 bolt	
Sensing input terminal (rear)	M4 screw	
Accessories	Instruction Manual, CD-ROM (Control Software, LabVIEW Driver, Instruction Manual for Remote Control and Control Software) Control cable (D-sub 25 pin connector)	

- *1 Can be set only in the polyphase output.

*2 For phase voltage setting in the polyphase output. In balanced mode all phases are collectively set and in unbalanced mode each phase is individually set .

*3 In the case of 10 V to 150 V/20 V to 300 V, sine wave, no load, 45 Hz to 65 Hz, DC voltage setting 0 V, 23°C±5C. For phase voltage setting in the polyphase output.

*4 Line voltage can be set only in balanced mode and sine wave.

*5 If the output voltage is higher than the rated value, this is limited (lowered) to satisfy the power capacity. If there is the DC superimposition, the active current of ACDC satisfies the maximum current. In the case of 40 Hz or lower or 400 Hz or higher, and that the ambient temperature is 40°C or higher, the maximum current may decrease.

*6 For the capacitor input type rectified load (crest factor=3), the rated output voltage, and 45 Hz to 65 Hz.

*7 In the case rated output voltage, 50 Hz or 60 Hz. If the output voltage is higher than the rated value, this is limited to satisfy the power capacity. It may reduce short reverse power flow if ambient temperature is 40°C or higher or repeated interval of reverse power flow is 15 minutes or less.

*8 External power injection or regeneration which is over short reverse power flow capacity is not available.

*9 For 45 Hz to 65 Hz, the rated output voltage, no load and the resistance load for the maximum current, and the operating temperature.

*10 For 40 Hz to 550 Hz, sine wave, the rated output voltage, the resistance load for the maximum current at 55 Hz, and 55 Hz reference.

*11 Setting for the L1 phase in the polyphase output. The component of the phase angle setting is added for the other phases.

*12 Can be set only with unbalance mode in the polyphase output.

*13 In the case of 50 V or higher, sine wave, and same load condition and voltage setting for all phases.
- *14 In the case of the AC mode and 23°C±5°C.

*15 In the case of -212 V to -10 V, +10 V to +212 V / -424 V to -20 V, +20 V to +424 V, no load, AC setting 0 V, 23°C±5°C.

*16 If the output voltage is higher than the rated value, this is limited (lowered) to satisfy the power capacity. If there is the AC superimposition, the active current of DC+AC satisfies the maximum current. In the case that the ambient temperature is 40 °C or higher, the maximum current may decrease.

*17 Instantaneous = within 2 ms, at the rated output voltage.

*18 In the case rated output voltage. If the output voltage is higher than the rated value, this is limited to satisfy the power capacity. It may reduce short reverse power flow if ambient temperature is 40°C or higher or repeated interval of reverse power flow is 15 minutes or less.

*19 For power input 170 V to 250 V (3P3W) or 323 V to 433 V (3P4W), power input 200 V reference (3P3W) or 380 V reference (3P4W), the resistance load at the maximum current, the rated output voltage, DC (only single-phase output) or 45 Hz to 65 Hz. Transition state immediately after a change of the input power-supply voltage is not included. For phase voltage setting in the polyphase output.

*20 In the case that the output current is changed from 0% to 100% of the maximum current. For output voltage 75 V to 150 V/150 V to 300 V, no load reference. However, if the output voltage is higher than the rated value, the maximum current is limited to satisfy the power capacity. For phase voltage setting in the polyphase output.

*21 For power input 200 V (3P3W) or 380 V (3P4W), no load, the rated output voltage, DC (only single-phase output) or 45 Hz to 65 Hz. For phase voltage setting in the polyphase output.

*22 40 Hz to 550 Hz, 50 % or higher of the rated output voltage, the maximum current or lower, AC and ACDC modes, THD+N.

*23 In the case of AC-INT, the rated output voltage, the resistance load at the maximum current, 45 Hz to 65 Hz output.

Note : The contents of this catalog are current as of July 2, 2019
*Products appearance and specifications are subject to change without notice.
*Before purchase contact us to confirm the latest specifications, price and delivery date.